

Manual Film Applicators

ZAF 2010

4-sided Applicator Frame

Versatility

The applicator frame can be used manually or in combination with automatic film applicators. Various width and thickness combinations (4 per version) are available.

Reliability

A significant advantage that the coating material being applied is retained within the guide walls, resulting in clean and precise applications.

Ease of Use

The film thickness can be easily chosen by placing the applicator with the desired thickness.



Processing Unit / Sensor

Measurement Modes	4 gap heights depending on version: 30 / 60 / 90 / 120 µm (1.18 / 2.36 / 3.54 / 4.72 mil) 50 / 100 / 150 / 200 µm (1.97 / 3.94 / 5.91 / 7.87 mil) or 4 on request from 5 - 2,000 µm (0.20 - 78.74 mil)
Measuring Geometries	Film Width depending on version: 60 mm (2.36") 80 mm (3.15") or on request from 20 mm to 200 mm (0.79" - 7.87")

SWISS MADE

Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.
www.screeningeagle.com

Request a quote

Machine translated & automatically generated (English version prevails):17.02.2022
Copyright © 2021 Screening Eagle Technologies AG or its affiliates. All rights reserved.